## **Uniform Mitigation Verification Inspection Form**

Maintain a copy of this form with the insurance policy

Inspection Date: 05/06/2011						
Owner Information						
Owner Name: BORDEAUX CONDOMIL	Contact Person:					
Address: 2431-2497 HERON TERRACE		Home Phone:				
City: CLEARWATER	Zip: 33761	Work Phone:				
County: PINELLAS		Cell Phone:				
Insurance Company:	I	Policy #:				
Year of Home: 1979	# of Stories: 2	Email:				
data I reported is true and correct.  1. Building Code: What building code w  ☐ A. 1994 South Florida Building Co Counties (also known as the High V ☐ B. Building code prior to the 1994 in Miami-Dade and Broward Coun ☐ C. 2001 Florida Building Code (bu	as used to design and build the strude (building permit application da Velocity Hurricane Zone (HVHZ)) South Florida Building Code (building permit application date of 3)	te of 9/1/1994 or later in Miami-Dade and Broward diding permit application date of 8/31/1994 or earlier				
the HVHZ).  E. Unknown or undetermined.  2. Predominant Roof Covering:  Permit Application Date: or Date of Installation:UNKNOWN  A. At a minimum meets the 2001 Florida Building Code or the 1994 South Florida Building Code and has a Miami-Dade NOA or FBC 2001 Product Approval listing demonstrating compliance with ASTM D 3161 (enhanced for 110MPH) OR ASTM D 7158 (F, G or H), OR FBC TAS 100-95 and TAS 107-95, OR FMRC 4470 and/or 4471 (for metal roofs).  B. Does not meet the above minimum requirements.  C. Unknown or undetermined.						
attribute marked in Sections 3 throug		le and accessible construction or mitigation n.				
3. Roof Deck Attachment: What is the weakest form of roof deck attachment?  ☑ A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift resistance of 55 psf.  ☐ B. Plywood/OSB roof sheathing with a minimum thickness of 7/16" attached to the roof truss/rafter (spaced a maximum of 24" o.c.) by 8d common nails spaced 6" along the edge and 12" in the fieldOR- Any system of screws, nails, adhesives other deck fastening system or truss/rafter spacing that has an equivalent mean uplift resistance of 103 psf.  ☐ C. Plywood/OSB roof sheathing with a minimum thickness of 7/16" attached to the roof truss/rafter (spaced a maximum of 24" o.c.) by 8d common nails spaced 6" along the edge and 6" in the fieldOR- Dimensional lumber/Tongue & Grooved decking with a minimum of 2 nails per boardOR- Any system of screws, nails, adhesives, other deck fastening system of truss/rafter spacing that has an equivalent mean uplift resistance of 182 psf.  ☐ D. Reinforced Concrete Roof Deck.						
Inspectors Initials WS Property Address	ss 2431-2497 HERON TERRA	ACE, CLEARWATER, Florida 33761				

\*This verification form is valid up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 02/10) Adopted by Rule 69O-170.0155 Page 1 of 4

	☐ E. Other:					
		F. Unknown or unidentified.				
	☐ G. No attic acc	☐ G. No attic access.				
4.	Roof to Wall Attachment: What is the weakest roof to wall connection?					
	☐ A. Toe Nails	Rafter/truss anchored to top plate of wall using nails driven at an angle through the rafter/truss and attached to the top plate of the wall.				
	☑ B. Clips	Metal attachments on every rafter/truss that are nailed to one side (or both sides in the case of a diamond type clip) of the rafter/truss and attached to the top plate of the wall frame or embedded in the bond beam.				
	☐ C. Single Wraps	Metal Straps must be secured to every rafter/truss with a minimum of 3 nails, wrapping over and secute to the opposite side of the rafter/truss with a minimum of 1 nail. The Strap must be attached to the togothe wall frame or embedded in the bond beam in at least one place.				
	☐ D. Double Wraps Both Metal Straps must be secured to every rafter/truss with a minimum of 3 nails, wrapping over and securing to the opposite side of the rafter/truss with a minimum of 1 nail. Each Strap must be attach to the top plate of the wall frame or embedded in the bond beam in at least one place.					
	☐ E. Structural	Anchor bolts structurally connected or reinforced concrete roof.				
	G. Unknown or					
	☐ H. No attic acc	ess				
5.	<b>Roof Geometry:</b> What is the roof shape(s)? (Porches or carports that are attached only to the fascia or wall of the host structure and not structurally connected to the main roof system are not considered in the roof geometry determination.)					
	☐ A. Hip Roof	Hip roof with no other roof shapes greater than 10% of the total building perimeter.				
	☑ B. Non-Hip Roo	f Any other roof shape or combination of roof shapes including hip, gable, gambrel, mansard and other roof shapes not including flat roofs.				
	☐ C. Flat Roof	Flat roof shape greater than 100 square feet or 10% of the entire roof, whichever is greater.				
6.	Gable End Bracing:	End Bracing: For roof structures that contain gables, please check the weakest that apply:				
	☐ A. Gable End(s) are braced at a minimum in accordance with the 2001 Florida Building Code.					
		t the above minimum requirements.				
	☐ C. Not applicable, unknown or unidentified.					
7.	Wall Construction T	Vall Construction Type: Check all wall construction types for exterior walls of the structure and percentages for each:				
	☐ A. Wood Frame	%				
	☐ B. Un-Reinforce	•				
	☑ C. Reinforced M	•				
	D. Poured Conci					
	☐ E. Other:	%				
8.	Secondary Water Ro	esistance (SWR): (standard underlayments or hot mopped felts are not SWR)				
	☐ A. SWR	Self adhering polymer modified bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed on insulation) applied as a secondary means to protect the dwelling from water intrusion.				
	☑ B. No SWR					
	C. Unknown or	undetermined.				

Inspectors Initials WS Property Address 2431-2497 HERON TERRACE, CLEARWATER, Florida 33761

•	<u>Opening Protection</u> : What is the <u>weakest</u> form of wind borne debris protection installed on the structure? (Exterior openings include, but are not limited to: windows, doors, garage doors, skylights, etc. Product approval may be required for opening protection devices without proper rating identification.)
	☐ A. All Exterior Openings (Glazed and Unglazed) All exterior openings are fully protected at a minimum with impact
	resistant coverings, impact resistant doors and/or impact resistant window units that are listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact". For the HVHZ, systems must have either a Miami-Dade NOA or FBC Approval marked "For Use in the HVHZ".
	☐ Miami-Dade County Notice of Acceptance (NOA) 201, 202 <u>and</u> 203. (Large Missile - 9 lb.)
	☐ Florida Building Code Testing Application Standard (TAS) 201, 202 <u>and</u> 203. (Large Missile – 9 lb.)
	☐ American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996. (Large Missile – 9 lb.)
	☐ Southern Standards Technical Document (SSTD) 12. (Large Missile – 9 lb.)
	☐ For Skylights Only: ASTM E 1886/E 1996. (Large Missile - 4.5 lb.)
	☐ For Garage Doors Only: ANSI/DASMA 115. (Large Missile – 9 lb.)
	B. <u>All exterior openings</u> are fully protected at a minimum with impact resistant coverings, impact resistant doors and/or impact resistant window units that are listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact":
	☐ ASTM E 1886 and ASTM E 1996. (Large Missile – 4.5 lb.)
	☐ SSTD 12. (Large Missile – 4 lb. to 8 lb.)
	☐ For Skylights Only: ASTM E 1886/E 1996. (Large Missile - 2 to 4.5 lb.)
	C. <u>All exterior openings</u> are fully protected at a minimum with impact resistant coverings, impact resistant doors and/or impact resistant window units that are listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Small Missile Impact":
	☐ Miami-Dade County NOA 201, 202 <u>and</u> 203. (Small Missile – 2grams)
	☐ Florida Building Code TAS 201, 202 <u>and</u> 203. (Small Missile – 2 grams)
	☐ ASTM E 1886 <u>and ASTM E 1996.</u> (Small Missile – 2 grams)
	☐ SSTD 12. (Small Missile – 2 grams)
	D. <u>All exterior openings</u> are fully protected with windborne debris protection devices that cannot be indentified as Miami-Dade or Florida Building Code (FBC) product approved. This does not include plywood/OSB or plywood alternatives (see Answer "H").
	All Glazed Exterior Openings
	☐ E. <u>All glazed exterior openings</u> are fully protected at a minimum with impact resistant coverings and/or impact resistant window units that meet the requirements of one of the standards listed in Answer "A" of this question. (Large Missile – 9 lb.)
	F. All glazed exterior openings are fully protected at a minimum with impact resistant coverings and/or impact resistant window units that meet the requirements of one of the standards listed in Answer "B" of this question. (Large Missile – 2 lb 8 lb.)
	G. <u>All glazed exterior openings</u> are fully protected at a minimum with impact resistant coverings and/or impact resistant window units that meet the requirements of one of the standards listed in Answer "C" of this question. (Small Missile – 2 grams)
	H. <u>All glazed exterior openings</u> are covered with plywood/OSB meeting the requirements of Section 1609 and Table 1609.1.4 of the 2004 FBC (with 2006 supplements).
	☐ I. <u>All glazed exterior openings</u> are fully protected with wind-borne debris protection devices that cannot be identified as Miami-Dade or FBC product approved. This does not include plywood/OSB or other plywood alternatives that do not meet Answer H (see Answer "K").
	None or Some Glazed Openings
	☑ J. At least one glazed exterior opening does not have wind-borne debris protection.
	☐ K. No glazed exterior openings have wind-borne debris protection. This includes plywood/OSB or plywood alternative systems that do not meet Answer "H".
	L. Unknown or undetermined.

Inspectors Initials WS Property Address 2431-2497 HERON TERRACE, CLEARWATER, Florida 33761

MITICATION INSPECTIONS MUST P	E CEDTIEIED DV 4 OU 41	IEIED II	NSDECTOD			
MITIGATION INSPECTIONS MUST B Section 627.711(2), Florida Statutes, provi	~					
Qualified Inspector Name: WILLIAM SEXTON	License Type: General building, or residential co	ontractor	License # or MSFH certificate #: CGC003886			
Inspection Company:		Phone:				
W.F. SEXTON, Inc.		727-385-9351				
Qualified Inspector – I hold an active license or c	ertificate as a: (check o	one)				
☐ Hurricane mitigation inspector certified by the My Safe Fl	orida Home Program.					
☐ Building code inspector certified under Section 468.607, Florida Statutes.						
☑ General, building or residential contractor licensed under	Section 489.111, Florida Star	tutes.				
☐ Professional architect licensed under Section 481.213, Flo	rida Statutes.					
☐ Professional engineer licensed under Section 471.015, Flo	rida Statutes.					
☐ Other individual or entity recognized by the insurer as possessing the necessary qualifications to properly complete this form pursuant to Section 627.711(2)(f), Florida Statutes.						
Individuals signing this form must have their license	or certificate in an "Act	tive" sta	itus at time of the inspection.			
I, WILLIAM SEXTON am a qualified inspector and I personally performed the inspection or had my employee () perform the inspection and I agree to be responsible for his/her work.						
Qualified Inspector Signature: Date:						
An individual or entity who knowingly provides or utters a false or fraudulent mitigation verification form with the intent to obtain or receive a discount on an insurance premium to which the individual or entity is not entitled commits a misdemeanor of the first degree (Section 627.711(3), Florida Statutes). The Qualified Inspector who certifies this form is strictly liable for all acts, statements, concealment of facts, omissions, and documentation provided by his or her employee who actually performed the inspection.						
Homeowner to complete: I certify that the named Qualified Inspector or his or her employee did perform an inspection of the residence identified on this form and that proof of identification was provided to me or my Authorized Representative.						
Signature:  An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to w of the first degree. (Section 627.711(3), Florida Statutes)		tion veri	fication form with the intent to			
The definitions on this form are for inspection purposes only and cannot be used to certify any product or construction feature as offering protection from hurricanes.						
Inspectors Initials WS Property Address 2431-2497 H	IEDONITEDDACE CLEA	RWATE!	R Florida 33761			

\*This verification form is valid up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 02/10) Adopted by Rule 69O-170.0155 Page 4 of 4





Photo 1 Photo 2





Photo 3 Photo 4



Elevation Photo 1



Elevation Photo 2



Elevation Photo 3



Elevation Photo 4



Elevation Photo 5



Elevation Photo 6



Elevation Photo 7



2497





Elevation Photo 9 2497





2497 2497





2497 2497